



Precision Bearing Industry Co., Ltd.

NTN 22332UAVS2 Bearing



Bearing No. 22332UAVS2

22332UAVS2 Bearing 2D drawings and 3D CAD models

Size	160x340x114 mm
Bore Diameter	160,000 mm
Outer Diameter	340,000 mm
Width	114,000 mm
d	160,000 mm
D	340,000 mm
H	114,000 mm
Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	54.18
EAN	4547359520293
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Bronze
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch - Metric	Metric
Long Description	160MM Straight Bore; 340MM Outside Diameter;



Precision Bearing Industry Co., Ltd.

	114MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	119.34
Outside Diameter	13.386 Inch 340 Millimeter
Width	4.488 Inch 114 Millimeter
Bore	6.299 Inch 160 Millimeter
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
bore diameter:	160 mm
operating temperature range:	-40 to 120 ° C
outside diameter:	340 mm
cage material:	Brass
overall width:	114 mm
bearing material:	Through Hardened Steel
bore type:	Straight
cage type:	Machined
outer ring type:	Not Split
precision rating:	Not Rated
internal clearance:	Upper 2/3 of C4 range
finish/coating:	Uncoated
closure type:	Open
outer ring width:	114 mm



Precision Bearing Industry Co., Ltd.

lubrication hole type:	Lubrication Groove & Hole
inner ring width:	114 mm
dynamic load capacity:	1330000 N
fillet radius:	4 mm
static load capacity:	1420000 N
series:	223
maximum rpm:	1200 rpm
manufacturer product page:	Click here